

MSDS ID: 8000138

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT PART NUMBER: 8000138
DESCRIPTION: XN THINNER

COMPANY:
Markem Corporation
150 Congress Street
Keene, NH 03431

EMERGENCY RESPONSE NUMBERS:
Transportation:
United States: (800) 424-9300
International: (703) 527-3887(collect)
Product Safety and Environmental:
(603) 352-1130

2. HAZARDOUS INGREDIENTS

COMPONENT	CAS #	PCT(WT)
Tributyl phosphate	126-73-8	80-100

Exposure and physical property information is presented in Section 9. If the total percentage is less than 100, the balance of this product is not considered to be hazardous as defined in the OSHA Hazard Communication Standard (29 CFR 1910.1200).

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS RATING SYSTEM
Health: 2
Flammability: 1
Reactivity: 0
Protection: B

NFPA RATING SYSTEM
Health: 2
Flammability: 1
Reactivity: 0

POTENTIAL HEALTH CONSIDERATIONS

LIKELY ROUTES OF ENTRY:
Contact; Inhalation

TARGET ORGANS:
Respiratory Tract;

POTENTIAL IMMEDIATE EFFECTS FROM OVEREXPOSURE

EYE CONTACT
Can cause minor eye irritation, tearing or reddening.

3. HAZARDS IDENTIFICATION (Cont.)

SKIN CONTACT

Can cause severe skin irritation, defatting, and dermatitis. Not likely to cause permanent skin damage.

SKIN ABSORPTION

No skin absorption hazard in normal industrial use.

INHALATION

Can cause respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

INGESTION

Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.

POTENTIAL LONG-TERM EFFECTS FROM OVEREXPOSURE:

CANCER INFORMATION

No IARC cancer hazard information available.
No ACGIH cancer hazard information available.
No NTP cancer hazard information available.
No OSHA cancer hazard information available.

REPRODUCTIVE SYSTEM INFORMATION

None of the substances in this product have been shown to cause reproductive system disorders.

ADDITIONAL HEALTH HAZARD INFORMATION

Tributyl phosphate: TBP was found not to be neurotoxic either acutely at 1000 mg/kg or after three months of exposure at up to 325 mg/kg/day. Assuming similar absorption of TBP by oral and inhalation routes of exposure and a breathing rate of approximately 170 mL/min, these values are approximately equivalent to inhalation exposures of 4900 mg/cu m acutely and 1590 mg/cu m per day subchronically. The ACGIH TLV (TWA) for TBP is 2.2 mg/cu m. This indicates that a minimum of a 700-fold safety factor exists for TBP as a potential neurotoxin(1). Large doses have been reported to cause dyspnea, weakness, pulmonary edema, and twitching in rats. Chronic inhalation of large doses can lead to general poisoning with paralysis, urinary bladder hyperplasia, and increased liver weight.(1) Healy, C.E.; Beyrouthy, P.C.; and Broxup, B.R., Am. Ind. Hyg. Assoc J. 56:349-355 (1995).

MEDICAL CONDITIONS POTENTIALLY AGGRAVATED BY OVEREXPOSURE

4. FIRST AID MEASURES

EYE CONTACT

Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Get immediate medical attention.

SKIN CONTACT

Wash with soap and water. Remove contaminated clothing and launder. Get

4. FIRST AID MEASURES (Cont.)

medical attention if irritation develops or persists.

INHALATION

Remove to fresh air. If not breathing, perform rescue breathing and, if available, have a trained person administer oxygen.

Get medical attention immediately.

INGESTION

Emergency personnel should be contacted immediately and be provided with this MSDS. For ingestion of small quantities of chemicals, the risk associated with inducing vomiting usually exceeds the poisoning risk.

5. FIRE FIGHTING MEASURES

FLAMMABILITY DATA

FLASH POINT: 239 F, 160 C

EXPLOSIVE/FLAMMABILITY LIMITS ESTIMATED FROM INGREDIENTS:

LOWER LIMIT: ND %

UPPER LIMIT: ND %

AUTOIGNITION TEMPERATURE ESTIMATED FROM INGREDIENTS:

770 F, 410 C

GENERAL HAZARDS

Material may ignite if heated to temperatures above the flash point in the presence of a source of ignition.

EXTINGUISHING MEDIA

Use alcohol foam, carbon dioxide (CO₂) or dry chemical. Water may not be effective to extinguish fire. Use water spray to cool fire-exposed containers and to protect personnel.

FIRE FIGHTING INSTRUCTIONS

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location. Heat may build pressure and rupture closed containers, spreading fire and increasing risk of burns or injuries. Use water spray/fog for cooling. Even if material is water soluble, it may not be practical to extinguish fire by water dilution. Notify authorities if liquid enters sewers or other public waters.

HAZARDOUS COMBUSTION PRODUCTS

carbon dioxide; carbon monoxide; phosphorus compounds

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEAN-UP PROCEDURES

Prevent the spread of any spill to minimize harm to human health and the environment. Dike with suitable absorbent material. Wear complete and proper personal protective equipment and ventilate the area.

HEALTH CONSIDERATIONS AND PROTECTIVE EQUIPMENT

6. ACCIDENTAL RELEASE MEASURES (Cont.)

Information on the selection and use of personal protective equipment is found in Section 8 of this MSDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; material spilled, quantity, the area in which it occurred and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits and consider that the evaporation of volatile solvents can lead to the displacement of air creating an environment that can cause asphyxiation.

7. HANDLING AND STORAGE

HANDLING

Avoid contact with material, avoid breathing vapors, use only in a well ventilated area.

STORAGE

Store in a cool, dry place. Isolate from incompatible materials.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

ENGINEERING CONTROLS

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to keep exposure to airborne contaminants below the TLV, PEL, or other recommended exposure limit and/or maintain operator comfort.

RESPIRATORY PROTECTION

If air monitoring indicates airborne concentrations at or above the limits, or symptoms of inhalation over-exposure occur, a respiratory protection program may be required. Engineering controls to reduce the exposure below acceptable limits are usually preferable to a respirator program.

EYE PROTECTION

Chemically resistant safety glasses with side shields must be worn when handling this product. Further eye protection such as chemical splash goggles and/or face shield must be worn when the possibility exists for eye contact due to splashing or spraying liquid or airborne particles. Contact lenses should not be worn. An eye wash station should be available.

SKIN PROTECTION

Depending upon conditions of use, wear protective gloves and other protective equipment. Inspect gloves for chemical break-through and replace as needed. Clean equipment thoroughly after each use.

Appropriate gloves to be used for MARKEM products that are mixtures have not been determined. Glove type(s) for ingredients present at 10% or more (if known) are:

Butyl rubber, Polyethylene,

 9. PHYSICAL AND CHEMICAL PROPERTIES - PRODUCT

APPEARANCE: Liquid
 COLOR: Colorless to pale amber
 ODOR: Characteristic
 SPECIFIC GRAVITY(g/ml): 0.98
 PERCENT VOLATILE: 100
 VOC CONTENT(lb/gal): Not determined
 VAPOR PRESSURE (Pa): Not determined
 BOILING PT OR RANGE(F): ND
 pH: NA
 VISCOSITY: ND
 VAPOR DENSITY: Heavier than air
 FREEZING POINT(F): ND
 EVAPORATION RATE: <0.01 (n-Butyl acetate = 1)

 9.1 EXPOSURE, PHYSICAL AND CHEMICAL PROPERTIES FOR COMPONENTS

COMPONENT	ACGIH		OSHA	
	TWA\CEIL	STEL	TWA	CEIL
126-73-8	0.2 ppm	NE	0.2 ppm	NE

COMPONENT CAS NUMBER	SPECIFIC GRAVITY	EVAP RATE N-BUTYL ACETATE=1	WATER SOLUBILITY Weight %	VAPOR PRESSURE mmHg at F
	126-73-8	0.980	<0.01	Negligible;

 10. STABILITY AND REACTIVITY

STABILITY

Stable under normal conditions.

CONDITIONS TO AVOID

Elevated temperatures in combination with sparks, open flames, or other sources of ignition.

INCOMPATIBILITY

strong oxidizing agents;

HAZARDOUS DECOMPOSITION PRODUCTS

carbon dioxide; carbon monoxide; phosphorus compounds

 11. TOXICOLOGICAL INFORMATION

Tributyl phosphate:

Acute toxicity:

Oral LD50 rat: 1390 mg/kg, Effect: kidney, ureter, bladder (changes in tubules)

Inhalation LC50 rat: 28 gm/m3/1H

Eye rabbit: 500 mg, Effect: Severe

 11. TOXICOLOGICAL INFORMATION (Cont.)

 12. ECOLOGICAL INFORMATION

No information available.

 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with all federal, state, local or provincial regulations.

 14. TRANSPORT INFORMATION, DOT and IATA:

DOT & IATA: NOT RESTRICTED

 15. REGULATORY INFORMATION

Those ingredients appearing on the following list that do not appear in Section 2 are present at <0.1% for carcinogens, <1% for other hazardous substances, or are not considered hazardous in this product.

UNITED STATES OF AMERICA

FEDERAL REGULATIONS

CERCLA: The following components have CERCLA reportable quantities:

CASRN	DESCRIPTION	CERCLA RQ	WEIGHT%
-------	-------------	-----------	---------

None

RCRA: The following components are subject to RCRA land disposal restrictions:

CASRN	DESCRIPTION
-------	-------------

None

SARA TITLE III

SECTION 302 Extremely Hazardous Substances (EHS)

CASRN	DESCRIPTION
-------	-------------

None

SECTION 311/312 Community Right to Know

CASRN	DESCRIPTION
-------	-------------

None

SARA HAZARD CATEGORY INFORMATION

FIRE: NO

SUDDEN RELEASE OF PRESSURE: NO

REACTIVE: NO

IMMEDIATE (ACUTE) HEALTH HAZARD: YES

DELAYED (CHRONIC) HEALTH HAZARD: YES

SECTION 313 Toxic Chemical Release Inventory Reporting (TRI)

CASRN	DESCRIPTION
-------	-------------

None

TSCA

SECTION 8(b) Inventory: All chemicals in this product appear in the inventory or are exempt from the listing requirements.

SECTION 12(b) Export: The following chemicals are subject to export reporting

 15. REGULATORY INFORMATION (Cont.)

CASRN	DESCRIPTION	
126-73-8	TRIBUTYL PHOSPHATE	
STATE REGULATIONS		
CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65)		
The following chemical(s) in this product are known to the State of California to cause cancer:		
CASRN	DESCRIPTION	WGT%
None		
The following chemical(s) in this product are known to the State of California to be hazards to reproductive health:		
None		
MASSACHUSETTS Right to Know Law		
CASRN	DESCRIPTION	%
126-73-8	TRIBUTYL PHOSPHATE	80-100
NEW JERSEY Right to Know Law		
CASRN	DESCRIPTION	%
126-73-8	TRIBUTYL PHOSPHATE	80-100
PENNSYLVANIA Right to Know Law		
CASRN	DESCRIPTION	%
126-73-8	TRIBUTYL PHOSPHATE	80-100

 16. OTHER INFORMATION

Note: A CAS number in the form TSXXXX-XX-X is a trade secret.

NA= Not applicable

ND= Not determined

TS= Trade secret

MSDS prepared by Richard C. Berry

This information is offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling practices are believed to be generally applicable, however each user must review the recommendations and determine the suitability for their intended use.